



007-036

M64X CONNECTOR HARNESS SET



Set of 3 coded AMP SEAL connectors pre-wired with 1.2 m cable 3 ft 11"
Connectors: Glass reinforced PBT Cable: PVC insulation
Connectors: Black (A), Grey (B), Black (C) Cable: Black with white core numbering
IP67 NEMA 6
-40 °C to +80 °C -40 °F to +176 °F
1.4 kg 3 lb 1 oz
AMP Connector (35 way) AMP Connector (35 way) AMP Connector (35 way) AMP Connector (35 way) Cable Length 1200 mm 47.24* Polyester Explanding Slieve (Black) AMP Connector (35 way) AMP Connector (35 way) Cable Length 1200 mm 47.24* Polyester Explanding Slieve (Black) AMP Connector (35 way) AMP Connector (35 way) Cable Length 1200 mm 47.24* Polyester Explanding Slieve (Black)
Heat shrink expanding sleeves to cables











DEEP SEA ELECTRONICS PLC UK

Highfield House, Hunmanby Industrial Estate, Hunmanby YO14 0PH TELEPHONE +44 (0) 1723 890099 FACSIMILE +44 (0) 1723 893303 EMAIL sales@deepseaplc.com WEBSITE www.deepseaplc.com

3230 Williams Avenue, Rockford, IL 61101-2668 USA
TELEPHONE +1 (815) 316 8706 FACSIMILE +1 (815) 316 8708
EMAIL sales@deepseausa.com WEBSITE www.deepseausa.com